

AKEMI® Colour Charts

Copyright © Akemi, 05/2017

Colour Matching System

Version: 01

WILSONART Stone Name	1. Wahl / 1st Choice					2. Wahl / 2nd Choice				
	Colour Code	Colour Bond ¹⁾ Adhesive Art. No.	Composil ²⁾ Silicon Art. No.	Akepox 5010 ³⁾ Adhesive Art. No.	Colour Code	Colour Bond ¹⁾ Adhesive Art. No.	Composil ²⁾ Silicon Art. No.	Akepox 5010 ³⁾ Adhesive Art. No.		
Antique White	1140 White	47015	40405	11462*	-	-	-	-		
Avalanche Melange	1160 White Magic	46112	40454	-	-	-	-	-		
Beige Tempest	1780 Beige Magic	46131	40456	-	-	-	-	-		
Chai Cream Mirage	1100 White	47011	40402	11462	1160 White Magic	46112	40454	-		
Coconut Oil	1160 White Magic	46112	40454	-	-	-	-	-		
Designer White	1100 White	47011	40402	11462	1160 White Magic	46112	40454	-		
Fossil Riverstone	1660 Cream	47067	40420	-	-	-	-	-		
Fresco Creta	1700 Beige	47071	40422	-	-	-	-	-		
Frosty White	1160 White Magic	46112	40454	-	-	-	-	-		
Graphite Mirage	1020 Black	47003	40408	11461	-	-	-	-		
Light Beige Mirage	1780 Beige Magic	46131	40456	-	-	-	-	-		
Meadow Melange	1660 Cream	47067	40420	-	-	-	-	-		
Mojave Melange	1780 Beige Magic	46131	40456	-	-	-	-	-		
Murano Creta	1640 Cream	47065	40418	-	-	-	-	-		
Natural Almond	-	-	-	-	1160 White Magic	46112	40454	-		
Oatmeal	1700 Beige	47071	40422	-	-	-	-	-		
Paris Fog	1815 Grey	47083	40434	-	1660 Cream	47067	40420	-		
Pisa Creta	-	-	-	-	1160 White Magic	46112	40454	-		
San Gabriel Riverstone	1700 Beige	47071	40422	-	-	-	-	-		
Sesame	1780 Beige Magic	46131	40456	-	-	-	-	-		
Venetian Creta	1700 Beige	47071	40422	-	-	-	-	-		
White Pepper	1780 Beige Magic	46131	40456	-	-	-	-	-		
Whitewater Riverstone	1700 Beige	47071	40422	-	-	-	-	-		
	-	-	-	-	-	-	-	-		

1) Epoxyacrylate Adhesive for **Indoor Application** only

2) **Engineered & Natural Stone** Silicone

3) Epoxy Adhesive for **Indoor & Outdoor Application**

* the mentioned **Colour Code** is **not available** in Akepox 5010, the shown Art. Nr. indicates the **closest Akepox 5010 colour**

The above information is based on the latest stage of our development and application technology. Due to a multiplicity of different influencing factors, this information - as well as other oral or written technical advises - must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece. Observation of Technical Data Instruction is mandatory (www.akemi.com).

AKEMI chemisch technische Spezialfabrik GmbH

90451 Nuremberg, Lechstraße 28, Germany

info@akemi.com

www.akemi.com